

NIGHT ROD® SPECIAL

VRSCDX



Massive Power Meets Cutting-edge Technology for a Nimble Ride that Takes Dark to Pitch Black

Model shown in HDI configuration.

The vehicle models, configurations, options, and accessories pictured or otherwise described in this reference guide may not be available in all countries.



Markets: AUS, BRZ, MEX, ENG, HDI, JPN

NIGHT ROD® SPECIAL

VRSCDX

MODEL OVERVIEW



MODEL OVERVIEW

The Night Rod® Special model is a sinister-looking machine with a Revolution® engine that delivers a V-Twin growl and massive power. It's styled for performance-minded enthusiasts who like a blacked-out, no-hassle ride, and an aggressive, drag-inspired riding position.

NEW IN 2016

- Paint color options and graphics

MODEL UNIQUE FEATURES

Style

- Black powder-coated engine with black covers
- Straight-shot exhaust with brushed finish dual mufflers; black end caps and exhaust shield
- Black Split 5-Spoke Cast Aluminum wheels with pinstripe
- Aggressively tapered tail section with flush-mount LED taillight
- Stylized, black speed screen visor
- Blacked-out frame, handlebar, front fork, triple clamps and covers
- Racing stripe featured on airbox and tail section (option)
- Sport front fender with painted brace supports
- Slim design, center license plate mount
- 240 mm wide rear tire
- Two-up seat with custom stitching

Fit

- Pull-back handlebar for improved rider ergonomics
- Reduced reach forward-mounted rider footpegs and controls; standard passenger footpegs
- Low, 675 mm seat height

MODEL UNIQUE FEATURES

Function

- Electronic speedometer with odometer, time-of-day clock on odometer, dual tripmeter, fuel gauge with low fuel warning light and countdown feature, low oil pressure indicator light, engine diagnostics readout, LED indicator lights, tachometer
- Hazard warning integrated into self-canceling turn signal controls
- Start, engine cutoff, left/right turn signals, horn, hi/low beam hand controls
- Electric power accessory connector under seat
- Two-up seat with flip-up fuel fill access
- Barrel key frame-mounted ignition; fork lock common with ignition key
- Re-tuned rear suspension for improved comfort
- Michelin® Scorcher® tires

Performance

- Rubber-mounted, liquid-cooled, 1250 cc Revolution® engine
- Electronic Sequential Port Fuel Injection (ESPFI) with heated O2 sensors
- 90kW @ 8000 RPM; 111Nm @ 7250 RPM
- Lightweight cast aluminum performance wheels
- Inverted front forks
- Dual front Brembo® disc brakes
- Anti-lock Braking System (ABS)¹, standard

¹ Harley-Davidson's independent Anti-lock Braking System is designed to help you maintain control during braking events, especially those that happen in less than optimum conditions. Engineering and styling worked together to make sure the system is not only designed and carefully tested to work superbly, but that it is also engineered not to interfere with style. ABS is standard on all 2016 V-Rod® motorcycles.

NIGHT ROD® SPECIAL

VRSCDX

MODEL SPECIFICATIONS¹



Specifications apply to all available markets unless noted.

| DIMENSIONS | |
|---|--|
| Length | 2440 mm (96 in.) |
| Overall Width | 890 mm (35 in.) |
| Overall Height | 1065 mm (41.9 in.) |
| Seat Height <i>(unladen)</i> | 675 mm (26.6 in.) |
| Ground Clearance | 115 mm (4.5 in.) |
| Rake <i>(steering head)</i> | 34° |
| Fork Angle | 34° |
| Trail | 142 mm (5.6 in.) |
| Wheelbase | 1705 mm (67 in.) |
| Tires <i>(Michelin® Scorcher® "11" front and rear):</i> | |
| • Front – Scorcher® "11" 120/70ZR-19 60W | |
| • Rear – Scorcher® "11" 240/40R-18 79V | |
| Fuel Capacity | 18.9 L (5 gal.) |
| <i>(warning light at approximately 1.9 L)</i> | |
| Oil Capacity <i>(w/filter)</i> | 4.7 L (5 qts.) |
| Coolant Capacity | 2.4 L (2.5 qts.) |
| Weight: | |
| • As Shipped 289 kg (637 lbs.) | |
| • In Running Order 302 kg (666 lbs.) | |
| • Gross Vehicle Weight Rating 488 kg (1075 lbs.) | |
| • Gross Axle Weight Rating | |
| • Front 171 kg (377 lbs.) | |
| • Rear 317 kg (698 lbs.) | |
| ENGINE | |
| Engine | Liquid-cooled, Revolution®, 60° V-Twin |
| Valves | Overhead cam, 4 valves per cylinder, solid tappet with shim-under-bucket lash adjustment |
| Bore x Stroke | 105 mm x 72 mm (4.13 in. x 2.835 in.) |
| Displacement | 1247 cc (76.1 cu. in.), 1246 cc (76.1 cu. in.) <i>(JPN)</i> |
| Compression Ratio | 11.5:1 |
| Fuel System² | Electronic Sequential Port Fuel Injection (ESPFI) |
| Air Cleaner | Down draft intake |
| Lubrication System | Wet-sump, integrated with powertrain crankcase |

| DRIVETRAIN | |
|------------------------|-----------------------------|
| Primary Drive | Gear, 64/117 ratio |
| Final Drive | Belt, 30/72 ratio |
| • MEX | Belt, 28/72 ratio |
| Clutch | 9-plate, wet, Assist & Slip |
| Transmission | 5-speed |
| Gear Ratios (overall): | |
| • 1st | 10.969 MEX 11.752 |
| • 2nd | 7.371 7.897 |
| • 3rd | 5.9 6.322 |
| • 4th | 5.095 5.459 |
| • 5th | 4.563 4.889 |

| CHASSIS | |
|----------------------------|---|
| Frame | Steel perimeter upper frame with hydroformed main rails and bolt-on lower frame rails; MIG welded |
| Swingarm | Polished, one-piece cast aluminum with black powder-coat finish |
| Front Forks | 43 mm inverted |
| Rear Shocks | Preload adjustable |
| Wheels: | Black, Split 5-Spoke Cast Aluminum with Pinstripe |
| • Front | 19 in. x 3 in. (483 mm x 76 mm) |
| • Rear | 18 in. x 8 in. (457 mm x 203 mm) |
| Brakes: | |
| • Caliper Type | 4-piston front and rear |
| • Rotor Type | Patented, one-piece floating rotor <i>(front)</i> , uniform expansion rotor <i>(rear)</i> |
| • Front <i>(dual)</i> | 300 mm x 5.1 mm (11.81 in. x 0.2 in.) |
| • Rear | 300 mm x 7.1 mm (11.81 in. x 0.28 in.) |
| • Anti-lock Braking System | Standard Optional <i>(MEX)</i> |
| Suspension Travel: | |
| • Front | 102 mm (4 in.) |
| • Rear | 74 mm (2.9 in.) |

| PERFORMANCE | |
|---------------------------------------|--|
| Engine Torque: | |
| • HDI <i>(per EEC/95/1)</i> | 111 Nm (81.9 ft-lb) @ 7250 RPM |
| • BRZ <i>(per EEC/95/1)</i> | 112 Nm (82.6 ft-lb) @ 7250 RPM |
| • MEX <i>(per J1349)</i> | 113 Nm (83.4 ft-lb) @ 6750 RPM |
| • JPN <i>(per EEC/95/1)</i> | 105 Nm (77.4 ft-lb) @ 7000 RPM |
| Lean Angle <i>(per J1168):</i> | |
| • Right | 32° |
| • Left | 32° |
| Fuel Economy³ | 6.3 L/100 km (37 mpg) |
| <i>ESPFI (EPA urban/highway test)</i> | |

| ELECTRIC | |
|---|--|
| Battery <i>(per Battery Council International Rating)</i> | Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca |
| Charging | Three-Phase, 38-amp system <i>(439W @ 13V, 2000 RPM, 489W max power @ 13V)</i> |
| Starting | 0.08 kW electric with direct drive starter motor engagement |
| Lights <i>(as per country regulation):</i> | |
| • Headlamp <i>(Quartz Halogen)</i> | 55-watt low beam, 60-watt high beam |
| • Tail/Stop Lights | 8W/28W reflector optics |
| • Indicator Lamps | High beam, neutral, low oil pressure, turn signals, engine diagnostics, security system⁴ <i>(optional - AUS, BRZ, MEX, ENG)</i> , coolant temperature, low fuel warnings, ABS <i>(HDI, JPN only)</i> |
| WARRANTY | |
| Warranty | 24 months <i>(unlimited mileage)</i> |
| Service Interval⁵ | First 1600 km (1000 miles), every 8000 km (5000 miles) thereafter |

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Recommended 91 octane or higher fuel (R+M)/2.

³ Standard and optional wheels may vary by country and region.

⁴ Values shown are nominal. Performance may vary by country and region.

⁵ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁶ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁷ Inspections of certain systems and components are required at 4000 km (2500 mile) intervals. See Owner's Manual for full details.

NIGHT ROD® SPECIAL

VRSCDX
COLORS/CALLOUTS



SOLIDS

Vivid Black

NEW Charcoal Denim *(shown)*

NEW Velocity Red Sunglo

NEW Olive Gold

* Availability of colors may vary from dealer to dealer, and is subject to change without notice.

Model shown in Domestic configuration.

